

喷嘴 入口 接头	流量 大小	喷嘴型号		材料代码			主体 入口 直径 (毫米)	额定 喷嘴 孔径 (毫米)	流量 (升/分钟)											喷流角度		
		CAA	A	BRASS	SS	316SS			0.2 巴	0.5 巴	1巴	1.5 巴	2巴	3巴	4巴	5巴	6巴	7巴	0.5 巴	1.5 巴	6巴	
1/8	0.5	●	●	●	●	●	0.79	1.2		0.2	0.2	0.3	0.3	0.4	0.5	0.5	0.6	0.6		58°	69°	
	1	●	●	●	●	●	1.6	1.6		0.3	0.5	0.6	0.6	0.8	0.9	1.1	1.1	1.2		64°	76°	
	2	●	●	●	●	●	2	2		0.6	0.9	1.1	1.3	1.6	1.8	2	2.2	2.4	52°	61°	69°	
	3	●	●	●	●	●	2.4	2.4		1	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	52°	64°	77°	
	5	●	●	●	●	●	3.2	3.2	1	1.6	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6	56°	67°	76°	
	8	●	●	●	●	●	4	4	1.6	2.6	3.6	4.5	5.2	6.3	7.3	8.2	8.9	9.6	56°	65°	70°	
	10	●	●	●	●	●	4.4	4.4	2	3.2	4.6	5.6	6.4	7.9	9.1	10	11	12	55°	65°	72°	
1/4	1	●	●	●	●	●	1.6	1.6			0.5	0.6	0.6	0.8	0.9	1	1.1	1.2		53°	67°	
	2	●	●	●	●	●	2	2		0.6	0.9	1.1	1.3	1.6	1.8	2	2.2	2.4		62°	71°	
	3	●	●	●	●	●	2.4	2.4		1	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	51°	65°	78°	
	5	●	●	●	●	●	3.6	3.6	1	1.6	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6	63°	73°	79°	
	8	●	●	●	●	●	4	4	1.6	2.6	3.6	4.5	5.2	6.3	7.3	8.2	8.9	9.6	61°	69°	73°	
	10	●	●	●	●	●	4.8	4.4	2	3.2	4.6	5.6	6.4	7.9	9.1	10	11	12	63°	70°	74°	
	15	●	●	●	●	●	5.9	5.2	3.1	4.8	6.8	8.4	9.7	12	14	15	17	18	63°	71°	72°	
3/8	5	●	●	●	●	●	3.6	3.2	1	1.6	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6	64°	73°	79°	
	8	●	●	●	●	●	4.4	4	1.6	2.6	3.6	4.5	5.2	6.3	7.3	8.2	8.9	9.6	62°	70°	74°	
	10	●	●	●	●	●	5.2	4.4	2	3.2	4.6	5.6	6.4	7.9	9.1	10	11	12	64°	72°	75°	
	15	●	●	●	●	●	5.9	5.6	3.1	4.6	6.8	8.4	9.7	12	14	15	17	18	64°	72°	74°	
	20	●	●	●	●	●	7.1	6.4	4.1	6.4	9.1	11	13	16	18	20	22	24	63°	70°	74°	
	25	●	●	●	●	●	7.5	7.5	5.1	8.1	11	14	16	20	23	25	28	30	63°	70°	74°	
1/2	30	●	●	●	●	●	8.3	7.9	6.1	9.7	14	17	19	24	27	31	33	36	63°	70°	74°	
	25	●	●	●	●	●	9.5	6.4	5.1	8.1	11	14	16	20	23	25	28	30	63°	66°	71°	
	30	●	●	●	●	●	9.5	7.5	6.1	9.7	14	17	19	24	27	31	33	36	67°	71°	75°	
	40	●	●	●	●	●	9.5	9.1	8.2	13	18	22	26	32	36	41	45	48	72°	76°	78°	
	50	●	●	●	●	●	9.5	11.1	10	16	23	28	32	39	46	51	56	60	74°	79°	82°	
60	●	●	●	●	●	9.5	13.1	12	19	27	33	39	47	55	61	67	72	77°	82°	86°		