

喷嘴 入口 接头	流量 大小	喷嘴型号		材料代码			额定 喷孔 孔径 (毫米)	最大 畅通 孔径 (毫米)	流 量 (升/分钟)										喷流角度		
		CAB	B	BRASS	SS	316SS			0.2 巴	1巴	1.5 巴	2巴	3巴	4巴	5巴	6巴	7巴	10 巴	0.5 巴	1.5 巴	6巴
1/8	2.8W	●	●	●	●	●	1.6	1		1.2	1.5	1.7	2	2.3	2.5	2.7	2.9	3.5	116°	120°	102°
	4.3W	●	●	●	●	●	2	1		1.9	2.3	2.6	3.1	3.5	3.9	4.2	4.5	5.4	116°	120°	102°
	5.6W	●	●	●	●	●	2.4	1	1.8	2.5	3.1	3.4	4	4.6	5.1	5.5	5.9	7.1	116°	120°	102°
	8W	●	●	●	●	●	2.4	1.3	2.6	3.6	4.4	4.8	5.8	6.6	7.2	7.8	8.4	10	116°	120°	103°
1/4	10W	●	●	●	●	●	2.8	1.3	3.3	4.5	5.5	6	7.2	8.2	9.1	9.8	11	13	116°	120°	103°
	12W	●	●	●	●	●	3.2	1.3	3.9	5.3	6.5	7.3	8.7	9.8	11	12	13	15	117°	120°	103°
	14W	●	●	●	●	●	3.6	1.6	4.6	6.2	7.6	8.5	10	12	13	14	15	18	117°	120°	103°
3/8	17W	●	●	●	●	●	4	1.6	5.6	7.6	9.3	10	12	14	15	17	18	22	117°	120°	103°
	20W	●	●	●	●	●	4.4	2.4	6.6	8.9	11	12	15	17	18	20	21	25	117°	120°	104°
	24W	●	●	●	●	●	4.8	2.4	7.9	11	13	15	17	20	22	24	26	31	117°	120°	104°
	27W	●	●	●	●	●	5.2	2.8	8.9	12	15	16	20	22	24	26	28	34	117°	120°	106°
1/2	30W	●	●	●	●	●	5.6	2.8	9.9	13	16	18	22	25	27	29	31	37	117°	120°	108°
	35W	●	●	●	●	●	6	3.2	12	16	19	21	25	29	32	34	37	44	117°	120°	108°
	40W	●	●	●	●	●	6.4	3.2	13	18	22	24	29	33	36	39	42	50	117°	120°	108°
	45W	●	●	●	●	●	6.4	3.6	15	20	25	27	33	37	41	44	48	57	117°	120°	110°
	50W	●	●	●	●	●	6.7	4	16	22	27	30	36	41	45	49	53	63	117°	120°	112°